Listing of Claims:

- 1. A building comprising Building consisting of at least one building part in a form of a freight container having side walls, a ceiling and a floor, characterized characterised in that, in the interior, a floor panel (3) loosely lies on the floor (4), the floor panel being which is several centimeters em smaller on all sides than interior dimensions defined by the inner walls.
- 2. A building Building according to claim 1, which consists of at least one building part in form of a freight container having side walls, a ceiling and a floor, characterized characterised in that, in the interior a floor panel (3) loosely lies on the floor (4), which is several cm smaller on all sides than the interior dimensions defined by the inner walls, and that in the clearance between an inner wall and a surrounding outer wall arranged spaced therefrom, profiled parts (20, 21) vertically aligned and telescoping with each other in pairs are arranged at a with lateral distance from to each other, the end pieces (20, 21) of which are each attached at the outer ceiling wall on the top or at the outer floor wall at the bottom, respectively.
- 3. A building Building according to claim 2, characterized characterised in that the profiled part attached at the floor extends as a hollow section part (21) across up to 1/4 of the distance between the ceiling and the floor and receives the profiled part (20) attached at the ceiling, which extends across about 9/10 of this distance.
- 4. A building Building according to claim one of the claims 2 or 3, characterized characterised in that the profiled parts (20, 21) are made of steel and are welded to the corresponding

attachment points.

- 5. <u>A building Building</u> according to <u>claim</u> at least one of the claims 2 to 4, <u>characterized</u> eharacterised in that the profiled parts (20, 21) are formed circular or as a square section with cross-sectional dimensions in the range of several <u>centimeters</u> eentimeters.
- 6. A building Wall and floor construction according to claim at least one of the claims 2 to 5, characterized characterised in that the telescoping movement is attenuated by means increasing friction at the mutually engaging surfaces of the profiled parts (20, 21).
- 7. A building Building according to claim at least one of the claims 1 to 6, characterized characterised in that the floor panel (3) is formed with fasteners (2) for the transport.